




# 00F5530E026

110 Delta Drive  
 Pittsburgh, PA 15238  
 NAFTA Sales: (1)800-245-3984  
 HK Sales : (852)3102-9337  
 magnetics@spang.com  
 www.mag-inc.com



Kool Mu Hf Permeability ( $\mu$ )	$A_L$ (nH/T <sup>2</sup> )	Core Marking	
		Lot Number	Part Number
26	138 ± 8%	XXXXXX	F5530E026

	Dimensions		Tolerance (±)			Packaging
	(mm)	(in)	(mm)	(in)		
A	54.86	2.159	0.81	0.032		Est. Box Qty= 96 Pcs
B	27.56	1.085	0.41	0.016		
C	24.61	0.969	0.38	0.015		
D	18.52	0.729	-	-	Min	Available Hardware
E	37.49	1.475	-	-	Min	PCB5530FA
F	16.76	0.660	0.38	0.015		
L	8.38	0.330	-	-	Nom	
M	10.29	0.405	-	-	Min	

Electrical Characteristics			Physical Characteristics					
Watt Loss @ 100 kHz, 100mT max (mW/cm <sup>3</sup> )	DC Bias min (oersteds)		Break Strength Min (kg)	Window Area $W_a$ (mm <sup>2</sup> )	Cross Section $A_e$ (mm <sup>2</sup> )	Path Length $L_e$ (mm)	Volume $V_e$ (mm <sup>3</sup> )	Est. Weight (Ea. Piece) (g)
	80%	50%						
425	110	200	57	381	417	123	51,300	156

Notes:	Temperature Rating
	Curie Temp: 500 °C

