




00F8024E060

110 Delta Drive
 Pittsburgh, PA 15238
 NAFTA Sales: (1)800-245-3984
 HK Sales : (852)3102-9337
 magnetics@spang.com
 www.mag-inc.com



Kool M μ Hf Permeability (μ)	A _L (nH/T ²)	Core Marking	
		Lot Number	Part Number
60	370 ± 8%	XXXXXX	F8024E060

	Dimensions		Tolerance (±)			Packaging
	(mm)	(in)	(mm)	(in)		
A	80.01	3.149	1.19	0.047		Est. Box Qty= 45 Pcs
B	24.13	0.950	0.64	0.025		
C	29.72	1.170	0.38	0.015		
D	14.02	0.552	-	-	Min	Available Hardware
E	59.28	2.333	-	-	Min	
F	19.81	0.780	0.38	0.015		
L	9.91	0.390	-	-	Nom	
M	19.81	0.780	-	-	Min	

Electrical Characteristics			Physical Characteristics					
Watt Loss @ 100 kHz, 100mT max (mW/cm ³)	DC Bias min (oersteds)		Break Strength Min (kg)	Window Area W _a (mm ²)	Cross Section A _e (mm ²)	Path Length L _e (mm)	Volume V _e (mm ³)	Est. Weight (Ea. Piece) (g)
	80%	50%						
425	30	80	59	555	600	131	78,840	233

Notes:	Temperature Rating
	Curie Temp: 500 °C

