




# 00G1808E040

110 Delta Drive  
 Pittsburgh, PA 15238  
 NAFTA Sales: (1)800-245-3984  
 HK Sales : (852)3102-9337  
 magnetics@spang.com  
 www.mag-inc.com



Edge Permeability ( $\mu$ )	$A_L$ (nH/T <sup>2</sup> )	Core Marking	
		Lot Number	Part Number
40	35 ± 8%	XXXXXX	G1808E040

	Dimensions		Tolerance (±)			Packaging
	(mm)	(in)	(mm)	(in)		
<b>A</b>	19.30	0.760	0.30	0.012		Est. Box Qty= 5700 Pcs
<b>B</b>	8.10	0.319	0.18	0.007		
<b>C</b>	4.78	0.188	0.15	0.006		
<b>D</b>	5.54	0.218	-	-	Min	Available Hardware
<b>E</b>	13.92	0.548	-	-	Min	PCB1808B1
<b>F</b>	4.78	0.188	0.13	0.005		00B180801
<b>L</b>	2.39	0.094	-	-	Nom	
<b>M</b>	4.65	0.183	-	-	Min	

Electrical Characteristics			Physical Characteristics					
Watt Loss @ 100 kHz, 100mT max (mW/cm <sup>3</sup> )	DC Bias min (oersteds)		Break Strength Min (kg)	Window Area $W_a$ (mm <sup>2</sup> )	Cross Section $A_e$ (mm <sup>2</sup> )	Path Length $L_e$ (mm)	Volume $V_e$ (mm <sup>3</sup> )	Est. Weight (Ea. Piece) (g)
525	80%	50%	2.3	51.5	22.8	40.1	914	3.61
	165	230						

Notes:	Temperature Rating
	Curie Temp: 500 °C

