




00G5528E060

110 Delta Drive
 Pittsburgh, PA 15238
 NAFTA Sales: (1)800-245-3984
 HK Sales : (852)3102-9337
 magnetics@spang.com
 www.mag-inc.com



Edge Permeability (μ)	A_L (nH/T ²)	Core Marking	
		Lot Number	Part Number
60	219 ± 8%	XXXXXX	G5528E060

	Dimensions		Tolerance (±)			Packaging
	(mm)	(in)	(mm)	(in)		
A	54.86	2.159	0.81	0.032		Est. Box Qty= 112 Pcs
B	27.56	1.085	0.41	0.016		
C	20.62	0.811	0.38	0.015		
D	18.52	0.729	-	-	Min	Available Hardware
E	37.49	1.475	-	-	Min	PCB5528WC
F	16.76	0.660	0.38	0.015		00B5528B1
L	8.38	0.330	-	-	Nom	
M	10.29	0.405	-	-	Min	

Electrical Characteristics			Physical Characteristics					
Watt Loss @ 100 kHz, 100mT max (mW/cm ³)	DC Bias min (oersteds)		Break Strength Min (kg)	Window Area W_a (mm ²)	Cross Section A_e (mm ²)	Path Length L_e (mm)	Volume V_e (mm ³)	Est. Weight (Ea. Piece) (g)
	80%	50%						
525	115	175	48	381	350	123	43,100	170.21

Notes:	Temperature Rating
	Curie Temp: 500 °C

