



00K160LE026

110 Delta Drive
 Pittsburgh, PA 15238
 NAFTA Sales: (1)800-245-3984
 HK Sales : (852)3102-9337
 magnetics@spang.com
 www.mag-inc.com



Kool M μ Permeability (μ)	A _L (nH/T ²)	Core Marking	
		Lot Number	Part Number
26	180 ± 8%	XXXXXX	K160LE026

	Dimensions		Tolerance (±)			Packaging
	(mm)	(in)	(mm)	(in)		
A	160.02	6.298	2.54	0.100		Box Qty= 16 Pcs
B	38.10	1.499	0.64	0.025		
C	39.62	1.559	1.27	0.050		
D	28.14	1.107	-	-	Min	Available Hardware
E	138.18	5.438	-	-	Min	
F	19.81	0.780	0.76	0.030		
L	9.91	0.390	-	-	Nom	
M	59.26	2.332	-	-	Min	

Electrical Characteristics			Physical Characteristics					
Watt Loss @ 100 kHz, 100mT max (mW/cm ³)	DC Bias min (oersteds)		Break Strength Min (kg)	Window Area W _a (mm ²)	Cross Section A _e (mm ²)	Path Length L _e (mm)	Volume V _e (mm ³)	Est. Weight (Ea. Piece) (g)
	700	80%						
	85	160	TBD	3,335	778	273	212,000	558

Notes:	Temperature Rating
	Curie Temp: 500 °C

