




00Y160LE026

110 Delta Drive
 Pittsburgh, PA 15238
 NAFTA Sales: (1)800-245-3984
 HK Sales : (852)3102-9337
 magnetics@spang.com
 www.mag-inc.com



| Kool M μ MAX Permeability (μ) | A _L (nH/T ²) | Core Marking | |
|--|--|--------------|-------------|
| | | Lot Number | Part Number |
| 26 | 180 ± 8% | XXXXXX | Y160LE026 |

| | Dimensions | | Tolerance (±) | | | Packaging |
|----------|------------|-------|---------------|-------|-----|--------------------|
| | (mm) | (in) | (mm) | (in) | | |
| A | 160.02 | 6.298 | 2.54 | 0.100 | | Box Qty= 16 Pcs |
| B | 38.10 | 1.499 | 0.64 | 0.025 | | |
| C | 39.62 | 1.559 | 1.27 | 0.050 | | |
| D | 28.14 | 1.107 | - | - | Min | Available Hardware |
| E | 138.18 | 5.438 | - | - | Min | |
| F | 19.81 | 0.780 | 0.76 | 0.030 | | |
| L | 9.91 | 0.390 | - | - | Nom | |
| M | 59.26 | 2.332 | - | - | Min | |

| Electrical Characteristics | | | Physical Characteristics | | | | | |
|--|---------------------------|-----|-------------------------------|---|---|---------------------------------------|---|-----------------------------------|
| Watt Loss @ 100 kHz, 100mT max (mW/cm ³) | DC Bias min (oersteds) | | Break Strength Min (kg) | Window Area W _a (mm ²) | Cross Section A _e (mm ²) | Path Length L _e (mm) | Volume V _e (mm ³) | Est. Weight (Ea. Piece) (g) |
| | 700 | 80% | | | | | | |

| Notes: | Temperature Rating |
|--------|--------------------|
| | Curie Temp: 500 °C |

