




00Y3515E060

110 Delta Drive
 Pittsburgh, PA 15238
 NAFTA Sales: (1)800-245-3984
 HK Sales : (852)3102-9337
 magnetics@spang.com
 www.mag-inc.com



Kool M μ MAX Permeability (μ)	A _L (nH/T ²)	Core Marking	
		Lot Number	Part Number
60	102 ± 8%	XXXXXX	Y3515E060

	Dimensions		Tolerance (±)			Packaging
	(mm)	(in)	(mm)	(in)		
A	34.54	1.359	0.51	0.020		Est. Box Qty= 840 Pcs
B	14.15	0.557	0.23	0.009		
C	9.35	0.368	0.18	0.007		
D	9.60	0.378	-	-	Min	Available Hardware
E	25.27	0.994	-	-	Min	PCB3515M1
F	9.32	0.367	0.20	0.008		PCB3515M2
L	4.45	0.175	-	-	Nom	00B351501
M	7.87	0.310	-	-	Min	

Electrical Characteristics			Physical Characteristics					
Watt Loss @ 100 kHz, 100mT max (mW/cm ³)	DC Bias min (oersteds)		Break Strength Min (kg)	Window Area W _a (mm ²)	Cross Section A _e (mm ²)	Path Length L _e (mm)	Volume V _e (mm ³)	Est. Weight (Ea. Piece) (g)
	80%	50%						
800	40	95	6.8	151	84.0	69.4	5,830	18.15

Notes:	Temperature Rating
	Curie Temp: 500 °C

