




Specification for:  
**0F42206TC**

110 Delta Drive  
Pittsburgh, PA 15238  
Phone: 412/696-1333  
Fax: 412/696-0333  
Email:magnetics@spang.com

**DIMENSIONS**



(mm)	Uncoated Nominal:	Min:	Max:
O.D. (A)	22.1	21.72	22.48
I.D. (B)	13.7	13.33	14.07
Ht. (C)	6.35	6.03	6.53

Eff. Parameters		
A <sub>e</sub> mm <sup>2</sup>	l <sub>e</sub> mm	V <sub>e</sub> mm <sup>3</sup>
26.2	54.1	1417

**INDUCTANCE**

AL value (nH/T <sup>2</sup> )	Test conditions
1812 ± 20%	10 kHz, 0.5 mT (For N = 5, use 0.8 mA), 25°C

**CORE LOSSES**

P <sub>L</sub> max	Production lot limit Max avg	Test conditions
312 mW (220 mW/cm <sup>3</sup> )	283 mW (200 mW/cm <sup>3</sup> )	25 kHz, 200 mT, 100°C
-	-	-

**COATING**

Uncoated
----------

**NOTE**

Spec. Modifications	Previous	Revised
2006.01.13	Losses: General F material	Losses : Detail as indicated