




Specification for:  
**0W41809TC**

110 Delta Drive  
 Pittsburgh, PA 15238  
 Phone: 412/696-1333  
 Fax: 412/696-0333  
 Email:magnetics@spang.com

**DIMENSIONS**



(mm)	Uncoated Nominal:	Min:	Max:
O.D. (A)	18.4	17.77	19.03
I.D. (B)	9.75	9.16	10.34
Ht. (C)	10.30	9.95	10.65

Eff. Parameters		
A <sub>e</sub> mm <sup>2</sup>	l <sub>e</sub> mm	V <sub>e</sub> mm <sup>3</sup>
43.1	41.4	1783

**INDUCTANCE**

AL value (nH/T <sup>2</sup> )	Test conditions
12200 ± 30%	10 kHz, 0.5 mT (For N = 5, use 0.21 mA), 25°C

**ELECTRICAL LOSSES**

tan δ / μ <sub>i</sub>	Production lot limit Average	Test conditions	
≤ 3.5 · 10 <sup>-6</sup>	≤ 3 · 10 <sup>-6</sup>	10 kHz	0.5 mT, 25°C
≤ 55 · 10 <sup>-6</sup>	≤ 45 · 10 <sup>-6</sup>	100 kHz	

**COATING**

Uncoated
----------

**NOTE**

Spec. Modifications	Previous	Revised
2006.01.11	LF: General W material	LF: Detail as indicated