



# EQH3222E026L152

110 Delta Drive  
 Pittsburgh, PA 15238  
 NAFTA Sales: (1)800-245-3984  
 HK Sales : (852)3102-9337  
 magnetics@spang.com  
 www.mag-inc.com



High Flux Permeability ( $\mu$ )	$A_L$ (nH/T <sup>2</sup> )	Core Marking	
		Lot Number	Part number
26	62 ± 8%	XXXXXX	EQH3222E026L152

	Dimensions		Tolerance (±)		Packaging
	(mm)	(in)	(mm)	(in)	
<b>A</b>	32.00	1.260	0.30	0.012	<b>Box qty: 240 pcs</b>
<b>B</b>	15.20	0.598	0.20	0.008	
<b>C</b>	22.00	0.866	0.30	0.012	
<b>D</b>	11.50	0.453	0.20	0.008	<b>Available Hardware</b>
<b>E</b>	27.60	1.087	0.30	0.012	
<b>F</b>	13.50	0.531	0.20	0.008	
<b>G</b>	20.43	0.804		Min	

Electrical Characteristics			Physical Characteristics					
Watt Loss @ 50 kHz, 100mT Nominal (mW/cm <sup>3</sup> )	DC Bias typical (Oe)		Break Strength Typical (kg)	Window Area $W_A$ (mm <sup>2</sup> )	Cross Section $A_e$ (mm <sup>2</sup> )	Path Length $L_e$ (mm)	Volume $V_e$ (mm <sup>3</sup> )	Weight (Ea. Piece) (g)
350	80%	50%	50	81.08	152.3	79.9	12,168	38.6
	260	460						

Notes:	Temperature Rating
	Curie Temp: 500°C

