



EQX3626E060L174

110 Delta Drive
 Pittsburgh, PA 15238
 NAFTA Sales: (1)800-245-3984
 HK Sales : (852)3102-9337
 magnetics@spang.com
 www.mag-inc.com



| XFlux Permeability (μ) | A_L (nH/T ²) | Core Marking | |
|------------------------------|----------------------------|--------------|-----------------|
| | | Lot Number | Part number |
| 60 | 144 ± 8% | XXXXXX | EQX3626E060L174 |

| | Dimensions | | Tolerance (\pm) | | Packaging | |
|----------|------------|-------|---------------------|-------|---------------------|---------------------------|
| | (mm) | (in) | (mm) | (in) | | |
| A | 36.00 | 1.417 | 0.40 | 0.016 | Box qty: TBD | |
| B | 17.40 | 0.685 | 0.20 | 0.008 | | |
| C | 26.00 | 1.024 | 0.30 | 0.012 | | |
| D | 13.40 | 0.528 | | | Typ. | Available Hardware |
| E | 32.00 | 1.260 | 0.30 | 0.012 | | |
| F | 14.40 | 0.567 | 0.20 | 0.008 | | |
| G | 22.30 | 0.878 | 0.30 | 0.012 | | |

| Electrical Characteristics | | | Physical Characteristics | | | | | |
|--|----------------------|-----|--------------------------|--------------------------------------|--|------------------------|---------------------------------|------------------------|
| Watt Loss @ 100 kHz, 100mT Nominal (mW/cm ³) | DC Bias Nominal (Oe) | | Break Strength min (kg) | Window Area W_A (mm ²) | Cross Section A_e (mm ²) | Path Length L_e (mm) | Volume V_e (mm ³) | Weight (Ea. Piece) (g) |
| TBD | 80% | 50% | TBD | 235.8 | 180.8 | 94.7 | 17,122 | TBD |
| | 115 | 190 | | | | | | |

| Notes: | Temperature Rating |
|--------|--------------------|
| | Curie Temp: 500°C |

